



**USTM**

Professional  
water treatment

## Automatic self-cleaning water filter AQWELL AUTO



**PRESSURE  
REDUCER**



**GLYCERIN  
MANOMETER**



**AUTOMATIC  
BACK-WASH**



- **Filtration of solid impurities: sand, rust, limescale, etc.**
- **Self-cleaning filter**
- **Backwash system with the auto module - automatic backwash function**
- **Integrated pressure reducer**
- **Can be installed on a vertical, horizontal and angled pipe.**
- **Universal connection 1" and 3/4" (both internal and external sizes)**
- **Twist & Clean system - cleaning the filter housing from the inside without turning off the water in the installation.**



### Operation of the Auto Aqwell controller

The device contains a drain valve and activates the flush - backwash. Once the filter backwash drain is connected to the sewer system, the device becomes maintenance-free. The controller can be programmed to backwash at intervals from 1 to 99 days. Rinse time can be set from 15 to 90 seconds. The controller has battery and power supply.



Technical specifications	
Input pressure	Max. 8 bar
Output pressure	Adjustable from 2-6 bar
Working pressure	Min. 1,5 bar
Working temperature	5 - 30°C
Connection size	¾" i 1"
Filtration accuracy	40 µm
Flow rate of filtered water	4 m³/h
Weight	2,3 kg
Dimensions	160 x 95 x 360 mm
Connection spacing	95mm (without half-screws)

### Replacement filters available



Set contents : aqwell, aqwell auto, power adapter, 1/4 hose, hose quick coupler, bracket, steel wrench, manual.