



USTM

Professional water treatment

MODERN, ECOLOGICAL AND ECONOMICAL SOFTENER

BLUES water softener

- DRY TANK OPTION GUARANTES LOWER SALT CONSUMPTION
- MODERN UP FLOW REGENERATION SYSTEM
- CHLORINE GENERATOR FOR AUTOMATIC DEVICE DISINFECTION
- SIMPLE AND INTUITIVE START-UP MAINTANACE OF THE DEVICE
- SALT LEVEL INDICATOR
- LANGUAGES: ENGLISH, POLISH, FRENCH



Symbol	WS-20-LCD-BLU-ES	WS-25-LCD-BLU-ES
Resine volume	20 l	25 l
Dimensions (width / deep / height)	33x45x111 cm	
Tank dimension (diameter / height)	8"/35"	10"/35"
Water temperature	4-30°C	
Working pressure	1,5-5 bar	
Power, voltage	230/12 V	
Power consumption	8 W	
Connection	1"	
Ion exchange capacity	57" dH x m ³	71" dH x m ³
Type of regeneration	volumetric time up flow	
Salt consumption for regeneration	2,8 kg	2,8 kg
Water consumption for regeneration	140 l	160 l
Nominal flow	1,2 (m ³ /h)	
Weight	34,5 kg	40 kg

AVAILABLE IN TWO SIZES OF 20 AND 25L