



## **WATER SOFTENER**

## micro

Primo Micro is the most compact softener.

Dedicated to small apartments, coffee shops and eateries.

The small size allows installation even in a tiny place.

Protects domestic appliances from scale and thus extends their service life. Increases effectiveness of detergents.



- attractive price
- high ion-exchange capacity
- modern automatic time/volume head
- intuitive display
- quiet and fast head operation
- adjusts water hardness with a mixer
- control plate protection against corrosion
- bypass and mixer included







devices protection against scale



increased efficiency of chemicals



extended service life of household appliances



## **TECHNICAL DATA**

Symbol	WS-06-ASD2-MICRO
Туре	Kompakt
Maximum flow	0,8 m³/h
Nominal flow	0,6 m³/h
Resin volume	4,5 l
Exchange capacity*1	13,5° dH x m³
Efficiency*2	1350 liters
Average water consumption for regeneration	37 l
Average salt consumption for regeneration	0,8 kg
Dimensions (W/D/H)	22 / 40 / 47 cm
Tank dimensions (OD/H)	7" / 13"
Weight	9,5 kg
Working pressure	3 – 5.5 bar
Working temperature	4 – 30 (°C)
Power supply, voltage	AC 220 - 240 V; 12 V (1500 mA)
Power consumption	8 W (nur während der Regeneration)
Connection	3/4"







 $<sup>^{\</sup>star 1}$  depends on water hardness;  $^{\star 2}$  at 10 dH (german hardness range)



Compact softeners are certified by NHI (National Institute of Hygiene). The certificate allows the device to come into contact with drinking water.

## **CONNECTION SCHEME**







